

TECHNICAL DATA SHEET

Rollgum® Cleaner



1. DESCRIPTION

Rollgum Cleaner has been designed for cleaning and conditioning EPDM and TPO waterproofing membranes, as well as the support surfaces where Rollgum accessories are applied before bonding or welding.



2. TECHNICAL SPECIFICATIONS

Solvents	Various solvents
Color	Colorless
Density at 20 °C	Approx. 0.7 g/cm ³
Flash Point:	-10 °C

3. APPLICATION INSTRUCTIONS

- Application with temperatures above 5 °C.
- To be used with cotton cloths.
- Do not use brushes or paint rollers.
- Excess product must be removed directly from surfaces.
- Use gloves and eye protection.
- Allow the product to evaporate before using other adhesives on the surfaces where it has been used.

4. PRESENTATION, STORAGE AND EXPIRATION

- Available in 5 L cans.
- Store in the original sealed container protected from sun, dust, moisture, and high temperatures. Clean and dry conditions below 35 °C. Not sensitive to cold.
- Unlimited shelf life when stored under the above conditions.

5. PRECAUTIONS

Consult the Safety Data Sheet (SDS) for safety advice.
Keep away from ignition sources - No smoking.

Our instructions are based on genuine laboratory studies and our experience, but we recommend that the person applying the product carry out their own tests, as the variety of materials on the market and the different application methods, over which we have no control, mean that said person is fully responsible for its application.